

About Xsens DOT

Xsens DOT is a state-of-the-art development platform for the measurement and analysis of human kinematics from industry leaders, Xsens. The platform features high-accuracy wearable inertial sensors, an easy-to-integrate mobile SDK and community support from Xsens experts.

Xsens DOT provides endless application possibilities for innovators and developers giving everything needed to build a commercially attractive application.

Make it happen with Xsens DOT

Visit www.xsens.com/xsens-dot



		ORIENTATION	
	Application dependent	STATIC	0.5° 1.0° 1 o RMS
SENSOR PLACEMENT	Straps available by Xsens (sold	(INCLINATION HEADING)	
	separately)	DYNAMIC	1.0° 2.0° lσ RMS
LATENCY	30 ms	(INCLINATION HEADING	
BATTERY	 70 mAh	SENSOR COMPONENTS	
	Charging time about 1 hr	FULL SCALE	± 2000°/s ± 16g ± 8 Gauss
WEIGHT	11.2 g	DIMENSIONS	3 axes
DIMENSIONS SENSOR	36.30 x 30.35 x 10.80 mm (l x w x h)		
OPERATING TEMPERATURE RANGE	0°C - 50°C		Orientation (Unit Quaternion: & Euler Angles)
			Free acceleration
WATERPROOF RATING	IP 68	DATA OUTPUT	Acceleration
INTERNAL STORAGE			Angular Velocity
	64 MB		Magnetic Field
COMMUNIC			Timestamp and status
			OUTPUT RATES
COMMUNICATION PROTOCOL	Best performance with Blue- tooth 5.0 devices	REAL-TIME	1Hz, 4Hz, 10Hz, 12Hz, 15Hz,
			20Hz, 30Hz and 60Hz
SUPPORTED MOBILE DEVICES	Android OS 8.0 or above iOS 9.0 or above	RECORDING	1Hz, 4Hz, 10Hz, 12Hz, 15Hz,
			20Hz, 30Hz, 60Hz and 120Hz
COMPATIBLE DEVICES	Any (via BLE 5.0)		